




# 台 宙 晶 體 科 技 股 份 有 限 公 司

## Top Crystal Technology Inc.,

### Power Light Source

Introduction :

THCA-DLI is one the highest flux LEDs in the world. Due to the special design of chip and package, the THCA-DLI is designed by particular package for high power LED



#### Feature :

- Long operating life
- Energy efficiency
- Low thermal resistance
- Compact design
- Instant light
- Fully dimmable
- Superior ESD protection
- ROHS compatibility


#### Typical Applications:

- CCTV
- Wireless communication





# 台 宙 晶 體 科 技 股 份 有 限 公 司 Top Crystal Technology Inc.,

## Package Dimensions:




Bottom Layout



Dimension

## Circuit Diagram



## Notes :

1. All dimensions are in millimeters
2. Tolerance is  $\pm 0.25\text{mm}$



# 台 宙 晶 體 科 技 股 份 有 限 公 司 Top Crystal Technology Inc.,

## **Absolute Maximum Ratings**

Parameter	Conditions	
DC Forward Current	1W	700mA
	3W	1000 mA
Peak Pulse Current (mA) (less than 1/10 duty cycle@1KHz)	1W	800 mA
	3W	1200 mA
LED Junction Temperature (°C)	120°C	
Operating Temperature (°C)	-30~80	
Storage Temperature (°C)	-40~100	
Soldering Temperature	Manual 240°C(max) 5 seconds	
Reverse Voltage	Not design to be driven in reverse bias	

## **Optical Characteristics (Tj=25°C)**

Color	Forward current	Dominant Wavelength $\lambda_d$		Viewing Angle Degree
		Min.	Max.	$2\theta_{1/2}$
IR850	700mA	840nm	870nm	125
	1000mA	840nm	870nm	125

Notes :

1. CCT (Wavelength)  $\pm 5\%$  tester tolerance.
2. Wavelength is measured with an accuracy of  $\pm 0.5\text{nm}$ .



# 台 宙 晶 體 科 技 股 份 有 限 公 司

## Top Crystal Technology Inc.,

### Flux Characteristics (T<sub>j</sub>=25°C)

Color	Forward current	Part Number	Minimum Luminous Flux(lm)	Typical Luminous Flux(lm)	Maximum Luminous Flux(lm)	Beam Pattern
IR850	700mA	THCA-DLIX	450mW	600mW	--	Lambertian
	1000mA	THCA-ELIX	630mW	800mW		

- TCI maintains a tolerance of  $\pm 7\%$  on flux and power measurements.
- Please do not drive at rated current more than 1 second without proper heat sink.

### Electrical Characteristics (T<sub>j</sub>=25°C)

Color	Forward current	Part Number	Forward Voltage V <sub>F</sub> (V)			Thermal Resistance Junction to lead (°C/W)
			Min.	Typ.	Max.	
IR850	700mA	THCA-DLIX	1.45	1.65	2.0	8
	1000mA	THCA-ELIX	1.5	1.8	2.3	

Notes:

1. V<sub>F</sub>  $\pm 0.1$ V tester tolerance.



# 台 宙 晶 體 科 技 股 份 有 限 公 司

## Top Crystal Technology Inc.,

### RELIABILITY ITEMS and SPECTIONS

Stress Test	Stress Conditions	Stress Duration	Failure Criteria
Room Temperature Operating Life (RTOL)	25°C, $I_F = \text{max DC}$ (Note 1)	1000 hours	Note 2
Wet High Temperature Operating Life (WHTOL)	85°C/60%RH, $I_F = \text{max DC}$ (Note 1)	1000 hours	Note 2
Wet High Temperature Storage Life (WHTSL)	85°C/85%RH, non-operating	1000 hours	Note 2
High Temperature Storage Life (HTSL)	110°C, non-operating	1000 hours	Note 2
Low Temperature Storage Life (LTSL)	-40°C, non-operating	1000 hours	Note 2
Non-operating Temperature Cycle (TMCL)	-40°C to 120°C, 30 min. dwell, <5 min. transfer	200 cycles	Note 2
Mechanical Shock	1500 G, 0.5 msec. pulse, 5 shocks each 6 axis		Note 3
Natural Drop	On concrete from 1.2 m, 3X		Note 3
Variable Vibration Frequency	10-2000-10 Hz, log or linear sweep rate, 20 G about 1 min., 1.5 mm, 3X/axis		Note 3
Solder Heat Resistance (SHR)	260°C $\pm$ 5°C, 10 sec.		Note 3
Solderability	Steam age for 16 hrs., then solder dip at 260°C for 5 sec.		Solder coverage on lead

#### Notes:

1. Depending on the maximum derating curve.
2. Criteria for judging failure

Item	Test Condition	Criteria for Judgement	
		Min.	Max.
Forward Voltage ( $V_F$ )	$I_F = \text{max DC}$	--	Initial Level x 1.1
Luminous Flux or	$I_F = \text{max DC}$	Initial Level x 0.7	--
Reverse Current ( $I_R$ )	$V_R = 5V$	--	50 $\mu A$

\* The test is performed after the LED is cooled down to the room temperature.


3. A failure is an LED that is open or shorted.




# 台 宙 晶 體 科 技 股 份 有 限 公 司

Top Crystal Technology Inc.,

## Color Spectrum, $T_J = 25^{\circ}\text{C}$



## Typical Spatial Radiation Pattern






# 台 宙 晶 體 科 技 股 份 有 限 公 司

## Top Crystal Technology Inc.,


### Light Output Characteristics

Relative Light Output vs. Junction Temperature at 700mA




### Forward Current Characteristics, $T_J = 25^\circ\text{C}$

Forward Voltage vs. Forward Current



Forward Current vs. Luminous Flux





# 台 宙 晶 體 科 技 股 份 有 限 公 司

## Top Crystal Technology Inc.,

### Moisture Sensitivity Level - JEDEC Level 3

Level	Floor Life		Soak Requirements			
			Standard		Accelerated Environment	
	Time	Conditions	Time (hours)	Conditions	Time (hours)	Conditions
3	168 hours	$\leq 30^{\circ}\text{C}$ / 60% RH	192 +5/-0	$30^{\circ}\text{C}$ / 60% RH	40 +1/-0	$60^{\circ}\text{C}$ / 60% RH

- The standard soak time includes a default value of 24 hours for semiconductor manufacture's exposure time (MET) between bake and bag and includes the maximum time allowed out of the bag at the distributor's facility.
- Table below presents the moisture sensitivity level definitions per IPC/JEDEC's J-STD-020C.

Level	Floor Life		Soak Requirements			
			Standard		Accelerated Environment	
	Time	Conditions	Time (hours)	Conditions	Time (hours)	Conditions
1	Unlimited	$\leq 30^{\circ}\text{C}$ / 85% RH	168 +5/-0	$85^{\circ}\text{C}$ / 85% RH	NA	NA
2	1 year	$\leq 30^{\circ}\text{C}$ / 60% RH	168 +5/-0	$85^{\circ}\text{C}$ / 60% RH	NA	NA
2a	4 weeks	$\leq 30^{\circ}\text{C}$ / 60% RH	696 +5/-0	$30^{\circ}\text{C}$ / 60% RH	120 +1/-0	$60^{\circ}\text{C}$ / 60% RH
3	168 hours	$\leq 30^{\circ}\text{C}$ / 60% RH	192 +5/-0	$30^{\circ}\text{C}$ / 60% RH	40 +1/-0	$60^{\circ}\text{C}$ / 60% RH
4	72 hours	$\leq 30^{\circ}\text{C}$ / 60% RH	96 +2/-0	$30^{\circ}\text{C}$ / 60% RH	20 +0.5/-0	$60^{\circ}\text{C}$ / 60% RH
5	48 hours	$\leq 30^{\circ}\text{C}$ / 60% RH	72 +2/-0	$30^{\circ}\text{C}$ / 60% RH	15 +0.5/-0	$60^{\circ}\text{C}$ / 60% RH
5a	24 hours	$\leq 30^{\circ}\text{C}$ / 60% RH	48 +2/-0	$30^{\circ}\text{C}$ / 60% RH	10 +0.5/-0	$60^{\circ}\text{C}$ / 60% RH
6	Time on Label (TOL)	$\leq 30^{\circ}\text{C}$ / 60% RH	Time on Label (TOL)	$30^{\circ}\text{C}$ / 60% RH	NA	NA






# 台 宙 晶 體 科 技 股 份 有 限 公 司

## Top Crystal Technology Inc.,

### Recommended Solder Pad Design




- All dimensions are in millimeters.
- Electrical isolation is required between Slug and Solder Pad



# 台 宙 晶 體 科 技 股 份 有 限 公 司

## Top Crystal Technology Inc.,

### Reflow Soldering Temperature Profile




Profile Feature	Typical parameters
Average Ramp-Up Rate ( $T_{s_{max}}$ to $T_p$ )	3 °C/second max.
Preheat Temperature Min ( $T_{s_{min}}$ )	150 °C
Preheat Temperature Max ( $T_{s_{max}}$ )	200 °C
Time ( $T_{s_{min}}$ to $T_{s_{max}}$ )	60-180 seconds
Time maintained above Temperature ( $T_L$ )	217 °C
Time maintained above Time ( $T_L$ )	60-150 seconds
Peak/Classification Temperature ( $T_p$ )	240 °C
Time within 5 °C of Actual Peak Temperature ( $T_p$ )	5 seconds
Ramp-Down Rate	6 °C/second max.
Time 25 °C to Peak Temperature	8 minutes max.

- All temperatures refer to topside of the package, measured on the package body surface.
- Repairing should not be done after the LEDs have been soldered. When repairing is unavoidable, a double-head soldering iron should be used. It should be confirmed beforehand whether the characteristics of the LEDs will or will not be damaged by repairing.
- Reflow soldering should not be done more than three times.
- When soldering, do not put stress on the LEDs during heating.
- After soldering, do not warp the circuit board.

## Tape and Reel Packaging Specifications

- Carrier Tape Dimensions



Notes:


1. Drawing not to scale.
2. All dimensions are in millimeters.
3. Unless otherwise indicated, tolerances are  $\pm 0.10\text{mm}$ .



# 台 宙 晶 體 科 技 股 份 有 限 公 司

## Top Crystal Technology Inc.,

- Reel Dimensions



Notes:

1. Empty component pockets sealed with top cover tape.
2. 1000 pieces per reel.
3. Drawing not to scale.
4. All dimensions are in millimeters



# 台 宙 晶 體 科 技 股 份 有 限 公 司

## Top Crystal Technology Inc.,

### Notice

- In order to avoid absorption of moisture, it is recommended that the products are stored in the dry box (or desiccators ) with a desiccants. Alternatively the following environment is recommended: Storage temperature : 5°C~30°C Humidity:60% HR max.
- If the storage conditions are of high humidity the product should be dried before use. Recommended drying conditions: 12 hours at 60°C±5°C.
- Any mechanical force or any excess vibration should be avoid during the cooling process after soldering.
- Reflow rapidly cooling should be avoided.
- Components should not be mounted on distorted Printed Circuit Boards.
- Devices should not contact with any types of fluid, such as water , oil , organic solvents.... etc.
- The maximum ambient temperature should be taken into consideration when determining the operating current.
- Devices should be soldered within 7 days after opening the moisture-proof packing.
- Repack unused product in anti-moisture packing, fold to close any opening and store in a dry place.
- The appearance and specifications of devices may be modified for improvement without notice.
- ESD Precautions Static Electricity and surge damages LEDs. It is recommended that wrist bands or anti-electrostatic gloves be used when handing the LEDs . All devices, equipment and machinery should be properly grounded.
- This product must be driven by constant power supplier.

### Handling of Silicone Lens LEDs

Notes for handling of silicone lens LEDs

- Please do not use a force of over 0.3kgf impact or pressure on the silicone lens, otherwise it will cause a catastrophic failure.
- The LEDs should only be picked up by making contact with the sides of the LED body.
- Avoid touching the silicone lens especially by sharp tools such as Tweezers.
- Avoid leaving fingerprints on the silicone lens.
- Please store the LEDs away from dusty areas or seal the product against dust.
- When populating boards in SMT production, there are basically no restrictions regarding the form of the pick and place nozzle, except that mechanical pressure on the silicone lens must be prevented.
- Please do not mold over the silicone lens with another resin. (epoxy, urethane, etc)



•